

# **APPENDIX**

**(Examples of Claim Conflicts between Applications)**

Comparison of claim 12 from Serial No. 08/469,626 to claim 24 from Serial No. 08/487,980.

Claim 12

A method of controlling a remote intermediate mass medium programming transmitter station to communicate mass medium program material to one or more receiver stations, with said remote transmitter station including a broadcast or cablecast transmitter for transmitting one or more units of mass medium programming, a plurality of selective transmission devices each operatively connected to said broadcast or cablecast transmitter for communicating a unit of mass medium programming, a mass medium programming receiver, a control signal detector, and a controller or computer capable of controlling one or more of said selective transmission devices, and with said remote transmitter station adapted to detect the presence of one or more control signals, to control the communication of specific units of mass medium programming in response to detected specific

Claim 24

A method of controlling a remote intermediate mass medium programming transmitter station to communicate mass medium program material to one or more receiver stations, with said remote transmitter station including a broadcast or cablecast transmitter for transmitting one or more units of mass medium programming, a plurality of selective transmission devices each operatively connected to said broadcast or cablecast transmitter for communicating a unit of mass medium programming, a mass medium programming receiver, a control signal detector, and a controller or computer capable of controlling one or more of said selective transmission devices, and with said remote transmitter station adapted to detect the presence of one or more control signals, to control the communication of specific units of mass medium programming in response to detected specific

control signals, and to deliver at its broadcast or cablecast transmitter one or more units of mass medium program, said method of communicating comprising the steps of:

(1) receiving a unit of mass medium programming to be transmitted by the remote intermediate mass medium programming transmitter station and delivering said unit of mass medium programming to a transmitter, said unit of mass medium programming having an instruct signal which is effective at the one or more receiver stations to *control a sequence of events*;

(2) receiving one or more control signals which at the remote intermediate mass medium programming transmitter station operate to control the communication of said unit of mass medium programming; and

(3) transmitting said one or more control signals to said

control signals, and to deliver at its broadcast or cablecast transmitter one or more units of mass medium program, said method of communicating comprising the steps of:

(1) receiving a unit of mass medium programming to be transmitted by the remote intermediate mass medium programming transmitter station and delivering said unit of mass medium programming to a transmitter, said unit of mass medium programming having an instruct signal which is effective at the one or more receiver stations to *decode a portion of a multichannel broadcast or cablecast transmission*;

(2) receiving one or more control signals which at the remote intermediate mass medium programming transmitter station operate to control the communication of said unit of mass medium programming; and

(3) transmitting said one or more control signals to said

transmitter before a specific time.

transmitter before a specific time.

Comparison of claim 24 from Serial No. 08/488,620 to claim 23 from Serial No. 08/477,660.

Claim 24

A method of controlling a computer to communicate a television signal in a television network, said network *having* a television transmitter station and a television receiver station, said receiver station having a computer for communicating of television signals, said method comprising the steps of:

programming *said receiver station* to search for data embedded in a television signal;

inputting an identifier code that designates a unit of computer software;

storing a television signal on a file storage medium at a storage device associated with said computer;

receiving from a remote source an information transmission that contains a control signal;

Claim 23

A method of controlling a computer to communicate a television signal in a television network, said network *comprised of* a television transmitter station and a television receiver station, said receiver station having a computer for communicating of television signals, said method comprising the steps of:

programming *a processor* to search for data embedded in a television signal;

inputting an identifier code that designates a unit of computer software;

storing a television signal on a file storage medium at a storage device associated with said computer;

receiving from a remote source an information transmission that contains a control signal;

selecting a storage location  
associated with said computer in  
response to said control signal;

transferring said unit of  
computer software to said storage  
device;

storing said unit of software  
on said file storage medium;

*executing* a technique for  
communicating a file stored on a  
disk associated with a computer;  
and

*communicating* said  
television signal in accordance  
with said technique.

selecting a storage location  
associated with said computer in  
response to said control signal;

transferring said unit of computer  
software to said storage device  
*and*

storing said unit of software on  
said file storage medium,

*thereby to enable said computer  
to execute* a technique for  
communication a file stored on a  
disk associated with a computer  
and

*communicate* said television  
signal in accordance with said  
technique.

Comparison of claim 23 from Serial No. 08/488,032 to claim 58 from Serial No. 08/451,746.

Claim 23

A method of communicating subscriber station information from a subscriber station to one or more remote data collection stations, said method comprising the steps of:

(1) inputting a viewer's or participant's reaction at a subscriber station;

(2) receiving at said subscriber station information that designates an instruct signal to process or an output to deliver in consequence of subscriber input;

(3) determining the presence of said subscriber input at said subscriber station by processing said viewer's or participant's reaction;

(4) processing an instruct signal which is effective to *coordinate data processing with communication or presentation* of television programming at said

Claim 58

A method of communicating subscriber station information from a subscriber station to one or more remote data collection stations, said method comprising the steps of:

(1) inputting a viewer's or participant's reaction at a subscriber station;

(2) receiving at said subscriber station information that designates an instruct signal to process or an output to deliver in consequence of *said specific* subscriber input;

(3) determining the presence of said *specific* subscriber input at said subscriber station by processing said viewer's or participant's reaction;

(4) processing an instruct signal which is effective to *receive, generate, or present output to supplement* television

subscriber station in consequence of said step of determining; and

(5) transferring from said subscriber station to one or more remote data collection stations an indicia confirming delivery of said instruct signal from said step of processing or confirming delivery of said effect from said step of processing.

programming at said subscriber station in consequence of said step of determining; and

(5) transferring from said subscriber station to one or more remote data collection stations an indicia confirming delivery of said instruct signal from said step of processing or confirming delivery of said effect from said step of processing.



Comparison of claim 47 from Serial No. 08/469,106 to claim 46 from Serial No. 08/487,649.

Claim 47

A method of controlling at least one of a plurality of receiver stations each of which includes a broadcast or cablecast mass medium program receiver, at least one output device, a control signal detector, at least one processor capable of responding to an instruct signal, and with each said mass medium program receiver station adapted to detect and respond to one or more instruct signals, said method of communicating comprising the steps of:

(1) receiving at a broadcast or cablecast transmitter station an instruct signal which is effective at the receiver station to *implement a scheme for generating a control signal* and delivering the instruct signal to a transmitter;

(2) receiving at said transmitter station one or more

Claim 46

A method of controlling at least one of a plurality of receiver stations each of which includes a broadcast or cablecast mass medium program receiver, at least one output device, a control signal detector, at least one processor capable of responding to an instruct signal, and with each said mass medium program receiver station adapted to detect and respond to one or more instruct signals, said method of communicating comprising the steps of:

(1) receiving at a broadcast or cablecast transmitter station an instruct signal which is effective at the receiver station to *select a broadcast or cablecast signalling scheme and generate a signal in consequence of said selected broadcast or cablecast signalling scheme* and delivering the instruct signal to a transmitter;

(2) receiving at said

control signals which at the receiver station operate to communicate the instruct signal to a specific processor; and

(3) transferring said one or more control signals to the transmitter, said transmitter transmitting the instruct signal and the one or more control signals.

transmitter station one or more control signals which at the receiver station operate to communicate the instruct signal to a specific processor; and

(3) transferring said one or more control signals to the transmitter, said transmitter transmitting the instruct signal and the one or more control signals.

Comparison of claim 11 from Serial No. 08/477,805 to claim 25 from Serial No. 08/449,523.

Claim 11

A method of controlling a remote television transmitter station to communicate television program material to one or more receiver stations, with said remote television transmitter station including a broadcast or cablecast transmitter for transmitting one or more units of television programming, a plurality of selective transmission devices each operatively connected to said broadcast or cablecast transmitter for communicating a unit of television programming, a television receiver, a control signal detector, and a controller or computer capable of controlling one or more of said selective transmission devices, and with said remote transmitter station adapted to detect the presence of one or more control signals, to control the communication of specific units of television programming in response to detected specific control signals, and to deliver at

Claim 25

A method of controlling a remote television transmitter station to communicate television program material to one or more receiver stations, with said remote television transmitter station including a broadcast or cablecast transmitter for transmitting one or more units of television programming, a plurality of selective transmission devices each operatively connected to said broadcast or cablecast transmitter for communicating a unit of television programming, a television receiver, a control signal detector, and a controller or computer capable of controlling one or more of said selective transmission devices, and with said remote transmitter station adapted to detect the presence of one or more control signals, to control the communication of specific units of television programming in response to detected specific control signals, and to deliver at

its broadcast or cablecast transmitter one or more units of television programming, said method of communicating comprising the steps of:

(1) receiving a unit of television programming to be transmitted by the remote intermediate television transmitter station and delivering said unit of television programming to a transmitter;

(2) receiving one or more control signals which at the remote intermediate television transmitter station operate to control the communication of *a specific one or more of said plurality of units* of television programming; and

(3) transmitting said one or more control signals to said transmitter before a specific time.

its broadcast or cablecast transmitter one or more units of television programming, said method of communicating comprising the steps of:

(1) receiving a unit of television programming to be transmitted by the remote intermediate television transmitter station and delivering said unit of television programming to a transmitter, *said unit of television programming having an instruct signal which is effective at the one or more receiver stations to implement a television signalling scheme;*

(2) receiving one or more control signals which at the remote intermediate television transmitter station operate to control the communication of *said unit* of television programming; and

(3) transmitting said one or more control signals to said transmitter before a specific time.